(11) Publication number:

KICOH LEGAL DIV.

06-178280

(4β)Date of publication of application : 24.06.1994

(51)Int.CI.

HO4N 7/13 HO3M 7/30 HO4N 1/41

(21)Application number : 04-\$51669

(71)Applicant: VICTOR GO OF JAPAN LTD

(22)Date of filing:

08.12.1992

(72)Inventor: TERANISHI YASUHIKO

(54) PICTURE INFORMATION CODER AND PICTURE INFORMATION DECODER

(57)Abstract:

PURPOSE: To reduce code quantity by terminating coding at a termination code when non-significant information obtained from output information of a scanning means or re-quantization of the output information continues to the end.

CONSTITUTION: An entropy coder 4 discriminates data and counts the number of consecutive 0s as a run length and allies 2-dimension Huffman coding by combining data not being zero and the run length of 0 data so far and stops scanning at an EOB code representing an end of a block when 0 data continues to its end. Then a coding signal bb obtained through a transmission line 5 and a demodulation means is decoded by an entropy decoder 6 in complementary relation to the entropy coder 4 and its output signal is fed to an inverse quantization device 8 via an inverse scanning means 7 implementing inverse scanning to the scanning means 3, in which inverse quantization is

applied and the resulting output signal is synthesized by

a synthesis filter bank 9 in complementary relation to a division filter bank 1 as an output picture digital signal cc and it is fed to the transmission line.

LEGAL STATUS

[Date of request for examination]

27.09.1995

Date of sending the examiner's decision of

rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

2980218

[Date of registration]

17.09.1999

[Number of appeal against examiner's decision

of rejection]

2005年 8月19日 17時22分

Searching PAJ

Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]

Conyright (C); 1998,2003 Japan Patent Office